

Signaling Units

Modular tower lights

Harmony type XVU Ø 60

Tower lights for customer assembly (up to 5 units)

Accessories




PF121716C

XVUC020



PF121723D

XVUZ01Q



PF154110A

XVUZ400



PF121725D

XVUZ05



PF154106A

XVUZ100T



PF121724C

XVUZ06



PF154109A

XVUZ12

Accessories					
Description	Voltage	Height of aluminium pole mm/in.	Color	Reference	Weight kg/lb
Body extender	≈ 24 V	–	Black	XVUC020	0.093/0.205
			Silver	XVUC020Q	0.093/0.205
Fixing unit, direct mounting	–	–	Black	XVUZ01 (2)	0.063/0.139
				XVUZ03 (1)	0.063/0.139
				XVUZ04 (3)	0.063/0.139
Fixing plate with aluminium pole	–	–	Black	XVUZ02	0.132/0.291
			Silver	XVUZ02Q	0.132/0.291
			Black	XVUZ400	0.236/0.520
			Black	XVUZ800	0.430/0.945
Fixing plate with height adjustment aluminium pole(4)	–	210 to 385/ 8.268 to 15.157	Black	XVUZ05	0.253/0.558
Flexible mounting unit for use on horizontal or vertical support, IP 55	–	–	Black	XVUZ06	0.193/0.425
Metal bracket with aluminium pole, IP42	–	–	Black	XVUZ100T	0.220/0.485
			Black	XVUZ250T	0.240/0.529
			Black	XVUZ400T	0.320/0.705
Fixing plate for use on vertical support	–	–	Black	XVUZ12	0.360/0.794

(1) Two-foot mounting
 (2) Three-foot mounting
 (3) Four-foot mounting
 (4) Only for use with DC body unit.