



Bilboquet

Designed by Philippe Malouin, 2023




LED retrofit - 7.5W

Table lamp with adjustable head. Integrated LED bulb and cut-off providing direct lighting . Body made of a special pigmented polycarbonate deriving from a byproduct of paper production rather than from petroleum. Adjustability through steel sphere treated with protective layer deposited in PVD. Useful length of the cable 2 mt. The cable can be adjusted and locked in place through a special slit in the base of the lamp. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607059210
Mounting	Table
Environments	Indoor dry location
Light Source Type	Bulb
Lamp category	LED retrofit
Lamp holders	GU10
Number of heads	1
Power (W)	7.5
System power (W)	7.5

Physical

Colour	Linen
Length (mm)	104
Cord length (mm)	2000
Net weight (kg)	1.8
Package height (mm)	95
Package width (mm)	300
Package length (mm)	380
Package volume (m3)	0.01
IP internal	20
IP external	20



LDT / IES

↓ ZIP















https://professional.flos.com/en/global/product/bilboquet-f0995017/

F0995017

Schematic light drawing



Beam	Beam Angle:	
h(m)	E(lx)	D(m)
1	571	1.01
2	143	2.02
3	63	3.02
4	36	4.03
5	23	5.04

Luminous flux luminaire 615 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-250
Dimmable	No
Dimming interface	Switch Integrated (Not Dimmable)
Plug type	Туре С



INCLUDED

RF35612

Non Dimable Bulb 2700K 7,5W 220-240V